

CYLINDERS

FOR USE WITH SCOTT SAFETY SELF-CONTAINED BREATHING APPARATUS



SCOTT SAFETY CYLINDERS

Over the years, breathing air cylinders have been providing SCBA users with a supply of fresh air. The original cylinders were made of steel and quite heavy. But today, advances in technology have enabled cylinders to become much lighter and less burdensome to the SCBA wearer. Scott offers a complete assortment of cylinders to meet the needs and demands of all SCBA users – aluminum cylinders for infrequently used SCBA to carbon-wrapped cylinders for daily use. In addition, Scott Safety offers cylinders in 30', 45', 60' and 75' durations (a Scott Safety exclusive).

5.5 CYLINDERS: THE LIGHTEST AND SMALLEST CYLINDERS USED ON SELF-CONTAINED BREATHING APPARATUS

The best way to understand the needs of Air-Pak SCBA users is to simply listen. Scott Safety did just that by visiting SCBA users from across North America. The participants included fire chiefs, SCBA technicians, safety officers and firefighters. It was not exclusive to the fire service as representatives from the military, general industry and law enforcement were also included. The overwhelming attribute that users requested was a reduction in weight followed closely by a reduction in profile.

The engineers of Scott Safety determined the best manner to accomplish this was to increase the pressure of the cylinders to 5500 psig, which created the new 5.5 cylinders, an "industry first." The result is a cylinder that has more than a 10% reduction in weight and profile in a traditional form familiar to SCBA users. Another benefit to the 5.5 cylinder offering is the ease of integration into your department without the need of costly infrastructure changes. Scott Safety has worked with leading Truck Seat and SCBA Bracket manufacturers to ensure these products work with the existing products in the market. The construction continues to be an aluminum liner wrapped with layers of carbon fibers and fiberglass all sealed with a protective epoxy resin coating which makes the cylinder easier to clean. The 5.5 cylinders are available in 30' 45', 60' and 75' durations.

The overall result is a lighter Air-Pak SCBA that reduces fatigue of the wearer, increases productivity and decreases injuries.



CYLINDER OFFERINGS

ALUMINUM CYLINDERS

- Scott Safety's Aluminum cylinders are built to the Department of Transportation (DOT) and Transport Canada (TC) specifications
- 2216 psig working pressure
- Rated for 30-minute duration based on NIOSH breathing rates
- Hydrostatic testing to be performed every five years
- Unlimited life expectancy

CARBON CYLINDERS

- Scott Safety's Carbon Cylinders are built to DOT and TC specifications
- 2216, 3000, 4500 and new 5500 psig working pressures
- Lightweight, composite cylinder consisting of an aluminum alloy inner shell with a total overwrap of carbon fiber, fiberglass and an epoxy resin
- Rated for 30', 45', 60' and 75' (5.5 only) durations based on NIOSH breathing rates
- Luminescent band provides greater visibility
- 75' cylinder is ideal for RIT and extended duration operations
- Hydrostatic testing to be performed every five years

ST7 TOUGH CYLINDERS

- Scott Safety's ST7 Tough Cylinders are built to DOT and TC specifications
- Built extremely tough and durable
- Provides added protection against abrasion and abuse
- 4500 psig working pressure
- Rated for 30', 45', and 60' durations based on NIOSH breathing rate
- Luminescent band provides greater visibility
- Hydrostatic testing to be performed every five years
- 15-year life expectancy

30-YEAR LIFE CYLINDERS

- Scott Safety's 30-Year Life Cylinders are built to DOT specifications
- 4500 psig working pressure
- Lightweight, composite cylinder consisting of an aluminum alloy inner shell with a total overwrap of carbon fiber, fiberglass and an epoxy resin
- Rated for 30', 45', and 60' durations based on NIOSH breathing rates
- Luminescent band provides greater visibility
- Hydrostatic testing to be performed every five years
- Up to a 30-year life expectancy

CYLINDER VALVES



CGA THREADED
CYLINDERS



ACS CYLINDERS



SNAP-CHANGE
CYLINDERS



ACCESSORY ITEMS:

CUSTOM LOGO I.D. BANDS

Scott Safety offers its customers the ability to customize their new carbon cylinders by adding a personalized logo. This custom logo is printed on white paper, and protected by the fiberglass wrap and epoxy resin.

- Maltese cross or Customer provided graphic
- Greater visibility
- Easy to identify
- Reduces cylinders being misplaced in mutual aid scenarios
- Twenty-five cylinder minimum order

To help prevent damage and improve durability of the cylinder, Scott Safety offers several protective solutions.

CYLINDER SLEEVES

Protective sleeves are offered for 2216 psi, 4500 psi, and 5500 psi carbon cylinders and will accommodate multiple cylinder sizes, to include 30', 45', and 60' rated durations.

- Constructed of a specially compounded fire retardant grade of clear, high durometer, PVC/Plastisol that meets or exceeds the flammability standards of the ASTM D-568
- Easy to use and install over the cylinder, forming a thick barrier and watertight seal
- Improves durability and extends cylinder life
- NFPA 1981, 2013 compliant as an accessory for our Air-Pak X3 SCBA and Air-Pak 75 SCBA

CYLINDER END CAPS

Protective end caps are offered for 4500 psi carbon cylinders and will accommodate 30' and 45' rated durations.

- Protects the crown areas of carbon cylinders
- Easy to install and remains firmly adhered to cylinder
- Easily removed and reused as necessary (i.e. hydrostatic testing)
- Can be purchased individually or as a set
- Improves durability and extends cylinder life
- NFPA 1981, 2013 compliant as an accessory for our Air-Pak X3 SCBA and Air-Pak 75 SCBA

CYLINDER SPECIFICATIONS

Description		Duration	Air Capacity		Volume	Dimensions			Weight	
Part Number	Pressure	Minutes (at 40 lpm)	SCF	Liters	H2O (in3)	Length in Inches (less Valve)	Length in Inches (with Valve)	Diameter in Inches	With Valve (Empty)	With Valve (Full)
CGA Threaded Cylinders										
Aluminum										
804101-01	2216	30	45	1274	517	20.95	24.05	6.75	17.85	21.29
Carbon-Wrapped										
804840-01	2216	30	45	1274	514	20.45	23.55	6.59	8.15	11.59
805044-01	3000	30	62	1756	521	20.70	23.80	6.78	10.35	15.09
804721-01	4500	30	45	1274	285	18.40	21.50	5.44	7.65	11.09
804722-01	4500	45	65	1841	418	20.30	23.40	6.26	10.05	15.02
804723-01	4500	60	87	2464	550	21.65	24.75	6.90	12.65	19.31
200930-01	5500	30	45	1274	223	19.10	22.20	4.94	6.84	10.28
200969-01	5500	45	66	1869	349	19.12	22.22	6.00	8.94	13.98
200972-01	5500	60	87	2464	465	21.43	24.53	6.53	11.04	17.69
200975-01	5500	75	111	3143	581	22.41	25.51	7.15	13.74	22.23
Carbon-Wrapped Short & Stubby										
804722-01A	4500	45	65	1841	416	18.00	21.10	6.79	10.35	15.32
Carbon-Wrapped ST7										
804721-11	4500	30	45	1274	285	18.40	21.50	5.47	7.75	11.19
804722-11	4500	45	65	1841	418	20.30	23.40	6.29	10.05	15.02
804723-11	4500	60	87	2464	550	21.60	24.70	6.93	12.75	19.41
Carbon-Wrapped 30-Year										
804721-35	4500	30	45	1274	285	18.40	21.50	5.49	8.05	11.49
804722-35	4500	45	65	1841	418	20.30	23.40	6.31	10.55	15.52
804723-35	4500	60	87	2464	550	21.65	24.75	7.00	13.95	20.61
Snap-Change Cylinders										
Carbon-Wrapped										
200131-01	2216	30	45	1274	514	20.45	23.70	6.59	8.50	11.94
200128-01	4500	30	45	1274	285	18.40	21.50	5.44	8.00	11.44
200129-01	4500	45	65	1841	418	20.30	23.40	6.26	10.40	15.37
200130-01	4500	60	87	2464	550	21.65	24.75	6.90	13.00	19.66
200967-01	5500	30	45	1274	223	19.10	22.20	4.94	7.15	10.59
200970-01	5500	45	66	1869	349	19.12	22.22	6.00	9.25	14.30
200973-01	5500	60	87	2464	465	21.43	24.53	6.53	11.35	18.01
200976-01	5500	75	111	3143	581	22.41	25.51	7.15	14.05	22.54
Carbon-Wrapped Short & Stubby										
200129-01A	4500	45	65	1841	416	18.00	21.30	6.79	10.70	15.67
Carbon-Wrapped ST7										
200128-11	4500	30	45	1274	285	18.40	21.50	5.47	8.10	11.54
200129-11	4500	45	65	1841	418	20.30	23.40	6.29	10.40	15.37
200130-11	4500	60	87	2464	550	21.60	24.70	6.93	13.10	19.76
Carbon-Wrapped 30-Year										
200128-35	4500	30	45	1274	285	18.40	21.50	5.49	8.40	11.84
200129-35	4500	45	65	1841	418	20.30	23.40	6.31	10.90	15.87
200130-35	4500	60	87	2464	550	21.65	24.75	7.00	14.30	20.96
ACS Cylinders										
Aluminum										
200874-01	2216	30	45	1274	517	20.95	24.05	6.75	18.00	21.44
Carbon-Wrapped										
200873-01	2216	30	45	1274	514	20.45	23.70	6.59	8.30	11.74
200870-01	4500	30	45	1274	285	18.40	21.50	5.44	7.80	11.24
200871-01	4500	45	65	1841	418	20.30	23.40	6.26	10.20	15.17
200872-01	4500	60	87	2464	550	21.65	24.75	6.90	12.80	19.46

© 2017 Scott Safety. SCOTT, the SCOTT SAFETY Logo, Scott Health and Safety and Air-Pak are registered and/or unregistered marks of Scott Technologies, Inc. or its affiliates.

Monroe Corporate Center • P.O. Box 569 • Monroe, NC 28111
 Telephone: 800.247.7257 • Facsimile: 704.291.8330
 www.scottsafety.com • sh-sale@tycoint.com

H/S 7012D_EN 3/17 ISO 9001 Registered. All rights reserved.

